

Gastronorm —

TG4 P PL TN

TG4 P PL BT

Catering

4 - Plastic-coated shelves GN 1/1 530 x 325 mm



Technical data

TG4 P PL TN

TG4 P PL BT

Gross volume	568 lt	568 lt
Working temperature	0 / +8 °C	-15 / -22 °C
Motor type	Plug-in	Plug-in
Refrigerant	R290	R290
Refrigeration power	369 W (-10°C / +45°C)	568 W (-25°C / +45°C)
Absorption	263 W	616 W
Voltage/Frequency	230V/1~/50Hz	230V/1~/50Hz

Energy data (UE Reg. 2015/1094)

Climate class	5 / (40°C - 40%)	5 / (40°C - 40%)
Type	This equipment is intended for use in ambient temperatures up to 40°C	

Energy data (UE Reg. 2015/1094)

Refrigeration unit	Tropicalized and easy extractable monoblock unit to guarantee reliability and performance at 43°C. Equipped with low consumption electronic fan motors	
Refrigerant charge	90 gr	95 gr
Evaporator	With cataphoresis anti-corrosion treatment	
Defrost	Automatic by air	Automatic by hot gas for a shorter cycle and less thermal shock
Condensate evaporation	Automatic through anti-corrosion treated compressor coil	

Construction details

TG4 P PL TN

TS4 P PL BT

Product dimensions WxDxH	2276x700x850	2276x700x850
Packaging dimensions WxDxH	2345x750x980	2345x750x980
Gross weight	200 Kg	206 Kg
Worktop	Sturdy and resistant stainless steel AISI 304 worktop with rounded edges	
Structure	Stainless steel AISI 304 monocoque	
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel	
Insulation thickness	50 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)	
Inner corners	Rounded for an easy cleaning	
Door	4 Self-closing doors with 120° door stop, reversibles on site	
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption	
Feet	AISI 304 stainless steel, height adjustable (135mm-230mm)	

Functions

Control panel	Compact, simple and intuitive touch screen display. Tilted control panel
---------------	--

Accessories

No. included accessories	4 - Plastic-coated grid GN 1/1 530x325 mm 4 - Pair of runners for grid 530x325 mm
--------------------------	--

Versions

Versions	Power supply frequency 60Hz
----------	-----------------------------

Technical datasheet EN
Updated on 17-12-2024